

## Falco Stucco Oil Putty

### Product Description

**Falco Stucco Oil Putty** is based on a blending of synthetic mixture resins. It is very easy to apply, giving a smooth coat with high adhesion to substrate. Specially designed to be used as a filler where Alkyd based Enamel will be used.

### Recommended Usage

To be used on interior and exterior surfaces of concrete, cement, plaster, gypsum board and wood works.

### Technical Data

Color	White		
Finish	Smooth / Matt		
Solid Content	53 % ± 2 by volume		
	Minimum	Maximum	Typical
Wet film thickness (microns)	166	250	208
Dry film thickness (microns)	100	150	125
Theoretical spreading rate (m <sup>2</sup> /ltr.)	6	4	4.8
Viscosity	Thick paste		
Specific gravity	1.60 ± 0.05 gm/cm <sup>3</sup>		
Drying time	Dry to touch (hours)		4
	Dry to recoat (hours)		8
Thinner / Cleaning	Fresh water		

### Hint

Theoretical spreading rate is a value that depends on solid content and desired dry film thickness by the following equation:

$$\text{Theoretical spreading rate} = \frac{10 \times \text{solid content by volume}}{\text{DFT in microns}}$$

### Application Data

#### Surface Preparation

The surface must be clean, dry and free from dust, oil, grease and any contaminations.

#### Tools

Putty knife.

#### Application Method

Apply two coats of **Falco Stucco Oil Putty** by putty's knife thinned with fresh water (10-15% by volume)

#### Recommended paint system for interior

- |                          |         |
|--------------------------|---------|
| • Falco Under Coat       | 1 coat  |
| • Falco Stucco Oil Putty | 2 coats |
| • Falco Lac Enamel       | 2 Coats |

**Note:** paint System may be varying according to the substrate.

### Packing size

- 1 liter, 1 US gallon and 5 US gallons steel cans (for local).
- 1 liter, 1 US gallon, 18 liters steel cans (for export).

### Storage

- The product should be stored in a dry, cool place and away from direct sun light.
- Cans should be well closed, classified according to the base and to be arranged by a maximum 3 plastic cans/row and 5 steel cans/row.

### Health and safety

- Inhalation Risks:

Vapor or mist can cause headache, nausea & irritation of the nose throat & lungs.

- Skin & Eye Contact:

Use good personal hygiene practices while working with this material. Dry contaminated clothing before reuse. For eye contact, flush with fresh water for at least 15 minutes. If irritation persists, get medical attention.

- Skin Absorption : Not expected.

- Ingestion Health Risks:

It may be harmful or fatal if swallowed. ingestion may cause nausea, vomiting & diarrhea. Consult a physician.

- Health Hazards : Acute & chronic (not expected).

- Emergency & First Aid Procedures:

- |               |                            |
|---------------|----------------------------|
| 1. Dermal     | : Clean with soap & water. |
| 2. Ingestion  | : Consult a physician.     |
| 3. Inhalation | : Remove to fresh air.     |

### Fire & Fire Fighting Data

- |                     |   |
|---------------------|---|
| Flash Point         | : 38° C.                                    |
| Flammable limits    | : None.                                     |
| Extinguishing media | : Foam, Alcohol Foam, CO2 and dry chemical. |

### Physical / Chemical Characteristics

- |                     |                      |
|---------------------|----------------------|
| Vapor Density       | : Heavier than air.  |
| Evaporation Rate    | : Slower than other. |
| Solubility in Water | : Soluble.           |
| Appearance/Odor     | : Paste, Mild Odor   |

For more information please refer to the Material Safety Data Sheet.