

Falco Floor Plaster repairing

Falco Floor Plaster repairing is a one component Polymer compound product. It is Fine powder product provides highly adhesion to the substrate. It consist of Portland cement, sand, lime, Polypropylene powder and Ethyl Cellulose providing highly impact resistance.

Recommended Usage

To be used (Repair all cracks & holes) for Internal & External floor substrate.

Technical Data

Appearance	Fine powder
Mixing ratio :	25 kg powder : 4 liter of water: 1 liter
Mixing instrument :	High speed mixture 3-5 minutes
Thickness :	2mm maximum
Clean Tools & Equipment :	Fresh water
Drying Time :	24 hours
Spreading rate :	3 m ² for 25kg @2mm

Application Data

Tools

Scraper.

Surface Preparation

The surface must be clean, dry and free from dust, oil, grease and any contaminations.

Application Method

Apply Falco Floor Plaster repair by scraper (after mixing with water by mixing machine).

Packing size

- 25 kgs bag (for local & export).

Storage

- The product should be stored in a covered storage away from direct sun light and excessive heat or cold.

Health and safety

- Inhalation Risks:

Vapor or mist can cause headache, nausea & irritation of the nose throat & lungs.

WATER BASE

- Skin & Eye Contact:

Use good personal hygiene practices while working with this material. Dry contaminated clothing before reuse. For eye contact, flush with fresh water for at least 15 minutes. If irritation persists, get medical attention.

- Skin Absorption: None expected.

- Ingestion Health Risks:

It may be harmful or fatal. If swallowed ingestion may cause nausea, vomiting & diarrhea. Consult a physician.

- Health Hazards : Acute & chronic (not expected).

- Emergency & First Aid Procedures:

1. Dermal : Clean with soap & water.
2. Ingestion : Consult a physician.
3. Inhalation : Remove to fresh air.

Fire & Fire Fighting Data

- Flash Point : None.
Flammable Limits : None.
Extinguishing Media : Foam, Alcohol Foam, Co2, Dry Chemical or Water.

Physical / Chemical Characteristics

- Vapor Density : Heavier than air.
Evaporation Rate : Slower than other.
Solubility in Water : Soluble.
Appearance & Odor : Paste, Mild Odor

For more information please refer to the Material Safety Data Sheet.