

# Falco Mezario

## Product Description

Falco Mezario is based on acrylic copolymer heavy textured water based product with marble chips and quartz granules. It is a weather and alkali resistance product. It is a decorative and protective "Scratched" patterned texture finish (MPI # 42).

## Recommended Usage

To be used as a top coat for exterior & interior concrete, plaster, gypsum and wood works. It is ideal for masonry surface and boundary walls.

## Technical Data

Color	White or as per our color card		
Finish	Heavy textured / Matt		
Solid Content	77% ± 2 by volume		
	Minimum	Maximum	Typical
Wet film thickness (microns)	1187	1428.5	1300
Dry film thickness (microns)	900	1100	1000
Theoretical spreading rate (m2/ltr.)	.86	.7	.77
Viscosity	Paste.		
Specific gravity	1.8 ± 0.05 gm/cm <sup>3</sup>		
Drying time	Dry to touch (hours)	2	
	Dry to recoat (hours)	8	
Thinner / Cleaning	Fresh water		

## Hint

Theoretical spreading rate is a value that depends on solid content and desired dry film thickness by the following equation:

$$\text{Theoretical spreading rate} = \frac{10 \times \text{solid content by volume}}{\text{DFT in microns}}$$

## Application Data

### Surface Preparation

The surface must be clean, dry and free from dust, oil, grease and any contaminations.

### Tools

Trowel.

### Application Method

Apply of one coat Falco Mezario (top coat) by trowel thinned with fresh water (max 10% by volume).

## WATER BASE

---

### Recommended paint system

- Falco Tex Primer 1 coat
- Falco Mezario 1 coat

**Note:** paint System may be varying according to the substrate.

### Packing size

- 1 US gallon and 5 US gallons plastic or steel cans (for local).
- 1 US gallon, 18 liters steel cans (for export).

### Storage

- The product should be stored in a dry, cool place and away from direct sun light.
- Cans should be well closed, classified according to the material's base and to be arranged by a maximum 3 plastic cans/row and 5 steel cans/row.

### Health and safety

- Inhalation Risks:  
Vapor or mist can cause headache, nausea & irritation of the nose throat & lungs.
- Skin & Eye Contact:  
Use good personal hygiene practices while working with this material. Dry contaminated clothing before reuse. For eye contact, flush with fresh water for at least 15 minutes. If irritation persists, get medical attention.
- Skin Absorption : None expected.
- Ingestion Health Risks:  
It may be harmful or fatal. If swallowed ingestion may cause nausea, vomiting & diarrhea. Consult a physician.
- Health Hazards : Acute & chronic (not expected).
- Emergency & First Aid Procedures:
  1. Dermal : Clean with soap & water.
  2. Ingestion : Consult a physician.
  3. Inhalation : Remove to fresh air.

### Fire & Fire Fighting Data

- Flash Point : None.
- Flammable Limits : None.
- Extinguishing Media : Foam, Alcohol Foam, Co2, Dry Chemical or Water.

### Physical / Chemical Characteristics

- Vapor Density : Heavier than air.
- Evaporation Rate : Slower than other.
- Solubility in Water : Soluble.
- Appearance & Odor : Viscous Texture, Mild Odor

For more information please refer to the Material Safety Data Sheet.